Office of the United States Trade Representative August 22, 2002

List of Additional Products to be excluded from the Section 201 Safeguard Measures, as established in Presidential Proclamation 7529 of March 5, 2002.

On March 5, 2002, the President issued Proclamation 7529, which established increases in duty and a tariff-rate quota (safeguard measures) pursuant to section 203 of the Trade Act on imports of certain steel products. See 67 FR 10553 (March 7, 2002). Proclamation 7529 also delegated to the USTR the authority to consider requests for exclusions of particular products and, upon publication in the Federal Register of a notice of his finding that a particular product should be excluded, to modify the HTS provisions created by the Annex to that Proclamation to exclude such particular product from the pertinent safeguard measure. In Proclamation 7576, dated July 3, 2002, the period provided in clause (5) of Proclamation 7529 was extended to allow for exclusion request review until August 31, 2002. See 67 FR 45285 (July 8, 2002). In accordance with the authority delegated in Proclamations 7529 and 7576, the following products will be excluded from the Section 203 safeguard measures when complete descriptions of these products are published in the forthcoming notice in the Federal Register.

Total: 178

Category	Number	One Line Description
		Forged fittings that are heat treated and produced to American specifications and
		European standards (e.g., normalized), with an annual quantity not exceed 3000 metric
Carbon Flanges/Fittings	X-063.0	tons.
		Certain Cold Drawn Special Shape Radius Edge Steel, .625" X 1.870" with .3125" radius
Cold Finished Bar	N323.01	edge Flat Bar, for use in Standard Ring, grade AISI 12L14
		Certain Cold Drawn Special Shape Radius Edge Steel, .562" X 1.562" with .281" radius
Cold Finished Bar	N323.02	edge Flat Bar, for use in Standard Ring, grade AISI 12L14
Cold Finished Bar	N361.02	HPM1 Prehardened Plastic and Rubber Mold Steel Cold Form Bar
Cold Finished Bar	N361.03	HPM1 Rough Machined Prehardened Plastic and Rubber Mold Steel Bar
Cold Finished Bar	N361.08	HPM1Cold Formed Rough Macined Prehardened Plastic and Rubber Mold Steel Bar
Cold Finished Bar	N387.02	Maraging Steel V726
Cold Finished Bar	N424.48	Cold Drawn freecutting valve block flat bar
Cold Finished Bar	N424.49	Cold finished C1018 carbon steel wide flat bar
Cold Finished Bar	N424.50	Cold drawn carbon steel Schumag flat bar, grade C1018
Cold Rolled Flat Rolled	N314.02	Cold rolled high carbon flat rolled steel, pickled with a carbon range of 0.45 to 0.55
		Cold-Rolled Steel for Flux-Cored Welding Wires, Category I,in widths 228 mm to 305
		mm; with an annual quantity not to exceed 15,000 (combined with N316.46 and
Cold Rolled Flat Rolled	N316.44	N316.49) metric tons.

		Cold-Rolled Steel for Flux-Cored Welding Wires, Category 3, in widths 228 mm to 305
		mm; with an annual quantity not to exceed 15,000 (combined with N316.44 and
Cold Rolled Flat Rolled	N316.46	N316.49) metric tons.
		Cold-Rolled Steel for Flux-Cored Welding Wires, Category 2, in widths 228 mm to 305
		mm; with an annual quantity not to exceed 15,000 (combined with N316.44 and
Cold Rolled Flat Rolled	N316.49	N316.46) metric tons.
Cold Rolled Flat Rolled	N335.01	Maraging steel, 18Ni-300 series, rolled in strip coil form
Cold Rolled Flat Rolled	N364.01	Cold Rolled low carbon continuous annealed EBT steel in coil.
		Cold-rolled low-carbon continuous-annealed steel in coil for small-diameter fluid-handling
		tubing for automotive and refrigeration applications with an annual quantity not to exceed
Cold Rolled Flat Rolled	N381.01	10,000 Metric Tons
Cold Rolled Flat Rolled	N387.07	75 NICR 4 for Foam Cutting Blades
		Certain cold-rolled drawing steel, carbon steel, of grade ASTM A1008 certification
		requirement to be determined and with an annual quantity not to exceed 20,000 metric
Cold Rolled Flat Rolled	N414.01	tons.
		Certain cold-rolled vitreous enamel carbon steel of grade ASTM A424, certification
Cold Rolled Flat Rolled	N414.04	requirement to be determined and in annual quantity not to exceed 15,000 metric tons.
		Ultra High Strength Cold Rolled Strip with 1.5 and 2.0 mm thickness, less than 500 mm
Cold Rolled Flat Rolled	N427.01	wide for the manufacture of safety critical formed automotive seat tracks
Cold Rolled Flat Rolled	N444.01	Certain Micro Alloyed Low Carbon Steel
Cold Rolled Flat Rolled	N444.02	Certain Micro Alloyed Low Carbon Steel
Cold Rolled Flat Rolled	N444.03	Certain Micro Alloyed Carbon Steel
Cold Rolled Flat Rolled	N444.04	Texture Rolled Steel Strip ("SORBITEX")
Cold Rolled Flat Rolled	N459.01	FB400 344F - Carbon Steel Flat Product
Cold Rolled Flat Rolled	N459.02	HF2 - 2AZ - Carbon Steel Flat Product
Cold Rolled Flat Rolled	N459.03	FB400 351F - Carbon Steel Flat Product
Cold Rolled Flat Rolled	N459.04	FB410 344F - Carbon Steel Flat Product
Cold Rolled Flat Rolled	N459.05	FB410 ZZ - Carbon Steel Flat Product
Cold Rolled Flat Rolled	N459.06	PBP2S - 351F - Carbon Steel Flat Product
Cold Rolled Flat Rolled	N459.07	SA153 Q Carbon Steel Flat Product
Cold Rolled Flat Rolled	N459.08	SA153 P4 Carbon Steel Flat Product
Cold Rolled Flat Rolled	N521.01	C1095 Steel strip-bread band knive quality
Cold Rolled Flat Rolled	N530.01	Cold-Rolled Saw Steel In Sheet Form, Grade DIN 1.2003, Through-Hardened
		B55 Cold Rolled, 55% Carbon Cold Rolled, Hardened and Tempered steel strip for
Cold Rolled Flat Rolled	X-010.11	printers rule, with an annual qauntity not to exceed 86 Metric tons.
Cold Rolled Flat Rolled	X-099.5	Cold rolled sheet in coils; 1.626 mm thick ASTM A715 grade "50" HSLA Steel
Corrosion Resistant	N316.45	Galfan ASTM A875 DDS IFS Boron-Treated Antibrittle Steel
Corrosion Resistant	N316.72	Galfan ASTM A875 IF-Rephosphorized Steel
		Galvannealed, interstitial-free carbon steel sheet in an annual quantity not to exceed
Corrosion Resistant	N346.02	80,000 metric tons

		Galvanized Steel Sheet In Coils, Less Than 3.25 Mm In Thickness. Astm A653/A653m-
		01
		C1008 Commercial With G30 Galvanized Coating; with annual quantity not to exceed
Corrosion Resistant	N406.06	9550 metric tons and certified to be used in the production of welded pipe or tube.
Concolorin Recolorant	11100.00	Continuous galvannealed and phosphate-coated (L-treated), extra deep-draw quality,
		single stabilized, interstitial-free, flat-rolled steel with a minimum mechanical elongation
Corrosion Resistant	N420.01	of 46% in a quantity not to exceed 4,000 metric tons.
Controsion Resistant	11420.01	Thin Hot-Dipped Alloy Corrosion-Resistant Steel (thickness range 0.248 mm to 0.330
Corrosion Resistant	N436.01	mm)
Corrosion Resistant	N437.01	River Zinc Black Chromate Coated Steel
Corrosion Resistant	N437.03	River Zinc Black Chromate Free Coated Steel
Conosion Resistant	11437.03	Electro-galvanized, drawing quality special killed, steel sheet in thickness greater than
Correction Desistant		
Corrosion Resistant	N465.08	2.06 mm utilized for critical internal automotive support components.
Corrosion Resistant	N469.01	Retained Austenite (TRIP) Steel, cold-rolled substrate, alloy, hot dip galvanized
Corrosion Resistant	N469.02	Complex phase steel, hot rolled substrate, alloy, electrogalvanized
Corrosion Resistant	N469.03	Retained Austenite (TRIP) Steel, cold-rolled substrate, alloy, electrogalvanized.
Corrosion Resistant	N469.04	Retained Austenite (TRIP) Steel, hot-rolled substrate, alloy, electogalvanized
Corrosion Resistant	N469.06	Partial Martensitic steel, cold-rolled substrate, alloy, electrtogalvanized.
Corrosion Resistant	N469.09	Complex phase steel, hot-rolled substrate, alloy, hot dip galvanized.
Corrosion Resistant	N469.10	Complex phase steel, hot-rolled substrate, alloy, electrogalvanized.
Corrosion Resistant	N469.11	Martenistic phase steel, hot rolled substrate, hot dip galvanized.
Corrosion Resistant	N469.12	Dual-phase steel, hot rolled substrate, alloy, electrogalvanized
Corrosion Resistant	N469.13	Martensitic phase steel, hot rolled substrate, electrogalvanized
Corrosion Resistant	N469.15	Partial Martenistic steel, cold-rolled substrate, alloy hot dip galvanized.
Corrosion Resistant	N476.01	Corrosion-resistant electrolytic steel coils containing a layer of phosphate
		Galvanized Dual Phase Coated Steel Products (Commonly referred to as: "RAGAL
Corrosion Resistant	X-146.0	LITEC DPF"), with annual quantity not to exceed 1000 metric tons.
Hot Rolled Bar	N339.01	Cutting edge sections also known as bevel flats
		1% Cr Mo V steel for bolting applications up to 570 degrees Celsius in power generation
Hot Rolled Bar	N354.03	turbines; an annual quantity not to exceed 100 metric tons.
Hot Rolled Bar	N361.06	HPM1 Hot-Rolled Prehardened Plastic and Rubber Mold Steel Bar
Hot Rolled Bar	N361.07	HPM1 Prehardened Plastic and Rubber Mold Steel Forged Bar
Hot Rolled Bar	N367.01	ASKO 93 Grade Hot Rolled Bar Used for Manufacture of Scrap Recycling Knives
		A specialized, high grade tool steel, known as Daido Steel's proprietary grade PX5, that
Hot Rolled Bar	N408.02	is used for construction of plastic molds
		A specialized, high grade tool steel, known as Daido Steel's proprietary grade NAK 80,
Hot Rolled Bar	N408.05	that is used for construction of plastic molds
	11100.00	A specialized, high grade tool steel, known as Daido Steel's proprietary grade NAK HH,
Hot Rolled Bar	N408.07	that is used for construction of plastic molds
	11-00.07	A specialized, high grade tool steel, known as Daido Steel's proprietary grade CX1, that
Hot Rolled Bar	N408.08	is used for construction of dies
	11-00.00	

		A specialized, high grade tool steel, known as Daido Steel's proprietary grade NAK 55,
Hot Rolled Bar	N408.10	that is used for construction of plastic molds
Hot Rolled Bar	N424.05	Hot-rolled Carbon Steel, grade ASTM A36, Near-Square Flat Bar (31.75 x 38.1)
Hot Rolled Bar	N424.07	Hot-Rolled Carbon Steel, grade ASTM A36, Near-square Flat Bar (44.45 x 50.8)
Hot Rolled Bar	N424.08	Hot-rolled Carbon Steel, grade ASTM A36, Near-Square Flat Bar (57.15 x 76.2)
Hot Rolled Bar	N424.09	Hot-rolled SBQ AISI C1018 Flat Bars
Hot Rolled Bar	N424.11	Hot-rolled Freecutting AISI 11L17 127 mm x 38.1 mm Flat Bar
Hot Rolled Bar	N424.14	Hot-rolled SBQ B26 Boron Alloy Steel Flats
Hot Rolled Bar	N424.16	Hot-rolled H & T MPI Tested Grade 4140 Alloy Flat Bar (76.2 x 63.5)
Hot Rolled Bar	N424.17	Hot-rolled Carbon Steel grade ASTM A36, Near-Square Flat Bar (76.2 x 114.3)
Hot Rolled Bar	N424.23	Hot-rolled Carbon Steel grade ASTM A36, Near-Square Flat Bar (44.45 x 63.5)
Hot Rolled Bar	N424.24	Hot-Rolled Carbon Steel grade ASTM A36, Near-Square Flat Bar (31.75 x 50.8)
Hot Rolled Bar	N424.31	Hot-rolled Carbon Steel grade ASTM A36, Near-Square Flat Bar
Hot Rolled Bar	N424.40	Hot-rolled Grade 4340 AlloySteel Flat Bar
Hot Rolled Bar	N424.45	Hot-rolled Carbon Steel, grade ASTM A36, Near-Square Flat Bar (63.5 x 76.2)
Hot Rolled Bar	N425.03	Hot-rolled AISI C1144 Flat Bars
Hot Rolled Bar	N438.02	Hot Rolled Bars (Ball Bearing Steel) under 47.625 mm in diameter
Hot Rolled Bar	N464.01	Hot rolled turned and polished steel bars per customer specs. In TLW-1.5752/3/00
Hot Rolled Bar	N464.03	Hot rolled turned and polished steel bars per customer spec. in TLW 1.7213.0.01
Hot Rolled Bar	N464.04	Hot rolled turned and polished steel bars per cutomer specs in TLW-1.6587.1.01
		Galvanized, cold formed, steel angles with yield strength 50,000psi to 65,000psi (350 to
Hot Rolled Bar	N495.02	450 Mpa), with an annual quantity not to exceed 300 MT.
		Galvanized, cold formed, steel Flats with yield strength 50,000psi to 65,000psi (350 to
Hot Rolled Bar	N495.04	450 Mpa)
		Special Bar Quality, BOP, Bloomcast ZF Grade 49, 25.4 mm – 76.2 mm Diameter, Cut
Hot Rolled Bar	N497.01	lengths and Round Bar in Coil Form
		Special Bar Quality, BOP, Bloomcast ZF Grade 34C, 1" – 3" Diameter, Cut lengths and
Hot Rolled Bar	N497.03	Round Bar in Coil Form
		Special Bar Quality, BOP, Bloomcast ZF Grade 15crmo5 1" to 3" diameter, cut lengths
Hot Rolled Bar	N497.04	and round bar in coil form (Abbreviated as description is too long)
		Special Bar Quality, BOP, Bloomcast ZF Grade 6, 1" – 3" Diameter, Cut lengths and
Hot Rolled Bar	N497.05	Round Bar in Coil Form
		Special Bar Quality (SBQ) Honda Motors Grade SCR420 (Carbon .17 to .23, Manganese
		.60 to 1.00, Phosphorus .20 max, Sulphur .025 max, Silicon .15 to .35), 1" to 3"
Hot Rolled Bar	N497.06	diameter, cut lengths and round bar in coil form
		API 5L Grade X-70 hot-rolled sheet in coil suitable for HIC-resistant applications in an
Hot Rolled Flat Rolled	N300.12	annual quantity not to exceed 10,000 MT (combined with 316.118)
Hot Rolled Flat Rolled	N310.01	SAE 1095 Fine grain with no more than 1 % gauge thickness decarb level
		Hot-Rolled American Pertoleum Institute Grade x56 Hydrogen Induced Cracking

Plate	N361.01	width less than 600mm and thickness 4.75 mm or more
		HPM1 Flat-Rolled Hot-Rolled Prehardened Plastic and Rubber Mold Steel Plate with
Plate	N316.57	ABROCLAD™ Plate (Tool Steel Clad on Carbon Steel)
Plate	N304.02	Hot-rolled plates for pipe forming to meet the chemical requirements of API 5L X-70
Hot Rolled Flat Rolled	X-099.2	30320361
		GRADES 045 AND 080 AND TRW RAW MATERIAL SPECIFICATION. TRW MS
		HOT ROLLED SHEET IN COILS; THICKNESS MORE THAN 3MM; ASTM A715
Hot Rolled Flat Rolled	X-038.0	(combined tonnage includes X-030 and X-068)
		BATTERY QUALITY HOT BAND with an annual quantity not to exceed 25,000 tons
Hot Rolled Flat Rolled	N457.04	DOMEX 120 Ultra High Strength Hot-Rolled Steel.
Hot Rolled Flat Rolled	N441.01	strength greater than or equal to 482 N/mm2, and hardness of 70 to 105 HRB.
		Hot-rolled sheet for coiled tubing used in high pressure oil and gas wells, with yield
Hot Rolled Flat Rolled	N381.02	Battery Quality Hot Band with an annual quantity not to exceed 1,310 Metric Tons
Hot Rolled Flat Rolled	N374.07	SAE J1392 O50 Temper Passed in an annual quantity not to exceed 1500 metric tons
Hot Rolled Flat Rolled	N374.03	tons
		Pickled and Oiled Flat Rolled Steel Coils in an annual quantity to exceed 4,000 metric
		ASTM A1011 DS Type B Modified (ASTM A622) SAE 1006 Hot Rolled or Hot Rolled
Hot Rolled Flat Rolled	N374.01	MT.
		Rolled Steel Coils that are Temper Passed, in an annual quantity not to exceed 4,000
	14210.90	ASTM A1011 DS Type A (Modified) Hot Rolled or Hot Rolled Pickled and Oiled Flat
Hot Rolled Flat Rolled	N316.98	Creusabro 4000®™ Cut-to-length Alloy Sheet
Hot Rolled Flat Rolled	N316.86	Hot-Rolled Dual Phase Low Silicon Content Usiphase D 80 Steel
Hot Rolled Flat Rolled	N316.85	Hot-Rolled Dual Phase Low Silicon Content Usiphase 1200 Steel
Hot Rolled Flat Rolled	N316.84	Hot-Rolled Dual Phase Low Silicon Content Usiphase 1200 Steel
Hot Rolled Flat Rolled	N316.65	Creusabro M™ Alloy Sheet
Hot Rolled Flat Rolled	N316.39	Hot-rolled American Pertoleum Institute Grade x80 High Resilience Steel
Hot Rolled Flat Rolled	N316.37	Hot-Rolled High Strength Multiphase Stampable Usiform 800 Steel
Hot Rolled Flat Rolled	N316.35	Hot-Rolled American Petroleum Institute Grade x70 High Resilience Steel
Hot Rolled Flat Rolled	N316.29	Hot-Rolled Dual Phase Low Silicon Content Usiphase D 60 Steel.
Hot Rolled Flat Rolled	N316.22	with an annual quantity not to exceed 10,000 MT.
I IOL RUIIEU FIAL RUIIEU	11310.21	Hot-Rolled Dual Phase Low Silicon Content Osiphase 1400 Steel. Hot-Rolled Presure Vessel Quality A 414 grade G Steel in Widths Greater than 2.03 m,
Hot Rolled Flat Rolled	N316.14 N316.21	Resistant (NACE) Steel. Hot-Rolled Dual Phase Low Silicon Content Usiphase 1400 Steel.
Hot Rolled Flat Rolled	N316.14	
Hot Rolled Flat Rolled	N316.120	Resistant (NACE) Steel in an annual quantity not to exceed 500 tons. Hot-Rolled American Petroleum Institute Grade x65 Hydrogen Induced Cracking
Hot Pollod Flat Pollod	N216 120	Hot-Rolled American Pertoleum Institute Grade x60 Hydrogen Induced Cracking
Hot Rolled Flat Rolled	N316.118	N300.12)
List Dallad Flat Dallad	N016 110	Resistant (NACE) Steel in an annual quantity not to exceed 10,000 MT (combined with
		Popietant (NACE) Staal in an annual guantity not to avaged 10,000 MT (combined with

		HPM1 Flat-Rolled Hot-Rolled Prehardened Plastic and Rubber Mold Steel Plate with
Plate	N361.04	width less than 600mm
		HPM1 Flat-Rolled Hot-Rolled Prehardened Plastic and Rubber Mold Steel Plate with
Plate	N361.05	width 600 mm or more
		HPM1 Flat-Rolled Hot-Rolled Prehardened Plastic and Rubber Mold Steel Plate with
Plate	N361.09	width 600 mm or more and thickness 4.75 mm or more
		A specialized, high grade tool steel, known as Daido Steel's proprietary grade NAK 55,
Plate	N408.01	that is used for construction of plastic molds
		A specialized, high grade tool steel, known as Daido Steel's proprietary grade PX5, that
Plate	N408.03	is used for construction of plastic molds
		A specialized, high grade tool steel, known as Daido Steel's proprietary grade NAK 80,
Plate	N408.04	that is used for construction of plastic molds
		A specialized, high grade tool steel, known as Daido Steel's proprietary grade NAK HH,
Plate	N408.06	that is used for construction of plastic molds
		A specialized, high grade tool steel, known as Daido Steel's proprietary grade CX 1, that
Plate	N408.09	is used for construction of plastic molds
		Higher yield strength structural steel plate for low temperature service, meeting the
Plate	N412.01	Canadian requirements of CAN/CSA S473.
		Plate for linepipe with a yield strength greater than or equal to 70000 psi, annual quantity
Plate	X-100.6	removed.
		Stainless steel angles meeting AISI 304 and 304L specifications, in sizes of 19.05mm x
SS Bar	N324.04	19.05mm x 3.175mm in all thicknesses.
		Stainless steel angles meeting AISI 316 and 316L specifications, in sizes including
SS Bar	N324.06	19.05mm x 19.05mm x 3.175mm in all thicknesses.
		Stainless steel angles, hot rolled, meeting AISI 304 and 304L specification, 19.05mm x
SS Bar	N353.03	19.05mm x 3.175mm, in all thicknesses.
		Stainless steel angles, hot rolled, meeting AISI 316 and 316L specifications, 19.05mm x
SS Bar	N353.04	19.05mm x 3.175mm, in all thicknesses.
SS Bar	N372.01	X90 Cold-Finished Stainless Steel Bar
		Kanthal APM electrical resistance bar and rod for use in industrial heating and household
SS Bar	N378.03	appliance elements.
		Kanthal Nikrothal 40 electrical resistance bar and rod for use in industrialheating and
SS Bar	N378.05	household appliance elements.

		Kanthal D electrical resistance bar and rod for use in industrial heating and household
SS Bar	N378.06	appliance elements.
		Kanthal AF electircal resistance bar and rod for use in industrial heating and household
SS Bar	N378.11	appliance elements.
		Kanthal A-1 electrcal resistance bar and rod for use in industrial heating and household
SS Bar	N378.13	appliance elements
SS Bar	N387.01	M300 High Chromium Mold Steel with annual quantity not exceeding 12 metric tons.
		PRODEC improved machining stainless steel cold finished bar in sizes less than 25.4
SS Bar	N389.01	mm; with an annual quantity not to exceed 2000 metric tons
		High Carbon martensitic engine valve steel with an annual quantity not to exceed 50
SS Bar	N395.02	metric tons
SS Bar	X-035.6	AF.918, solution annealed, stainless steel bar
		UGIMA® (Ugine Improved Machinability) stainless steel bar (in an annual quantity not to
SS Bar	X-090.020	exceed 5000 metric tons)
		Kanthal DT electrical resistnace wire for use in industrial heating and household
SS Wire	N378.02	appliance elements.
		Kanthal Nikrothal 40 electrical wire for use in industrial heating and household appliance
SS Wire	N378.04	elements.
		Kanthal A electical resistance wire for use in industrial heating and household appliance
SS Wire	N378.07	elements.
		Kanthal D electrical resistance wire for use in industrial heating and household appliance
SS Wire	N378.08	elements.
		Kanthal APM electrical resistance wire for use in industrial heating and household
SS Wire	N378.09	appliance elements.
		Kanthal A-1 electircal resistance wire for use in industrial heating and household
SS Wire	N378.12	appliance elements
		Kanthal Alkrothal 14 electrical resistance wire for use in industrial heating and household
SS Wire	N378.14	appliance elements.
		Kanthal AF electrical resistance wire for use in industrial heating and household
SS Wire	N378.15	appliance elements.
SS Wire	N470.01	SMX-90 Rectangular or Shaped wire for piston ring

SS Wire	N470.02	SUS420J2 Rectangular or shaped wire for piston ring
SS Wire	N470.03	SMX-70 Regtangular or shaped wire for piston ring
		Stainless steel wire, drawn and annealed in Canada from stainless steel wire rod, not
SS Wire	X-053.0	shaved or peeled.
		PRODEC improved machining stainless hot rolled, solution annealed and descaled wire
		rod in sizes less than or equal to 25.4 mm, with annual quantity not to exceed 500 metric
SS Wire Rod	N389.02	tons.
	11000.02	Tin Mill Black Plate, Single Reduced, 65 base weight, for use in the manufacturing of
Tin Mill Flat Rolled	N333.01	pencil ferrules and other, small, drawn parts
	11000.01	Tin Mill Black Plate, Single Reduced, 60 Base weight, for use in the manufacturing of
Tin Mill Flat Rolled	N333.02	engine gaskets
	11333.02	
		Single Reduced Tin Coated Steel 1108.0750 mm Wide Used to Produce D&I Two-Piece
Tip Mill Flot Dollad	N200.02	0
Tin Mill Flat Rolled	N390.02	Cans (in combination with N390.07 in a quantity not to exceed 30,000 metric tons)
		Circle Deduced Tip Costed Steel 072 1975 rpm Wide Head to Draduce D&I Two Diago
	1000 07	Single Reduced Tin Coated Steel 973.1375 mm Wide Used to Produce D&I Two-Piece
Tin Mill Flat Rolled	N390.07	Cans.(in combination with N390.02 in a quantity not to exceed 30,000 metric tons)
		Electrolytic Tin Plate, in widths greater than 1072 mm, with certification requirement to
Tin Mill Flat Rolled	N428.01	be determined and in annual quantity not to exceed 860 metric tons
		Tin mill black plate in widths greater than 1073.150 with certification requirement to be
Tin Mill Flat Rolled	N428.02	determined and in an annual quantity not to exceed 760 metric tons
Tin Mill Flat Rolled	N526.01	ETP EOLE End stock (min elongation of 3%)
Tin Mill Flat Rolled	N526.02	Tin-Free EOLE End Stock (min elongation of 3%)
Tin Mill Flat Rolled	N526.03	ETP EOLE End Stock (min elongation of 3%)
		Single reduced tin coated steel for D & I cans, width of 858.8 mm; to be included under
Tin Mill Flat Rolled	X-160.1	the 36,000 MT quantity limitation established in the X-160.3 exclusion on June 17, 2002.
Welded Pipe &		Rectangular and Square Stainless Steel Tubes, with an annual quantity not exceed 5
Tube(Other than OCTG)	N319.02	metric tons.
		Welded steel process pipes for atmospheric and lower temperatures, high pressure
Welded Pipe &		service at moderate and high temperatures ASTM Grades A671, A672, and A691, with
Tube(Other than OCTG)	N397.01	outside diameters from from 18 inches to less than 24 inches.
		Submerged Arc Welded structural steel pipe for structural applications manufactured to
Welded Pipe &		meet API specification 2B; and ASTM Grade A252, for structural applications, in specific
Tube(Other than OCTG)	N397.02	diameter and wall thickness combinations.
Welded Pipe &	1001.02	
Tube(Other than OCTG)	N449.01	Shinto Calorized ceramic coated lance pipe
Welded Pipe &	10.01	Welded Large Diameter Line Pipe Over 24 inches in outside Diameter, grade X 70 or
Tube(Other than OCTG)	N485.02	higher, with annual quantity not to exceed 100,000 metric tons.
Welded Pipe &	11403.02	Welded Drawn Over Mandrel Tubes for Swaged or Straight Propshafts with certification
	X 162 2	
Tube(Other than OCTG)	X-162.2	requirement to be determined

Welded Pipe &		Welded Drawn Over Mandrel Tubes For Shock Absorbers with certification requirement
Tube(Other than OCTG)	X-162.3	to be determined
Welded Pipe &		Welded Drawn Over Mandrel Tubes for Gas Springs with certification requirement to be
Tube(Other than OCTG)	X-162.4	determined

In addition to the products excluded today, the following products will also be excluded through amendments to the scope of the relevant tariff headings: certain stainless steel angles, shapes and sections of greater than 80 millimeters, and certain hydraulic fittings.